

2000

BowTech Bow Specifications

Model	Brace	String	Cable 1	Cable 2	Cam Type	Mod Type															
						23.5	24.0	24.5	25.0	25.5	26.0	26.5	27.0	27.5	28.0	28.5	29.0	29.5	30.0	31.0	32.0
G3	6	88 3/8	38 5/8	18 3/4	FM				FM6		FM5		FM4		FM3		FM2		FM1		
G3	7	88 3/8	38 5/8	18 3/4	FM						FM6		FM5		FM4		FM3		FM2	FM1	
BK2	5.5	55 3/4	37 1/4	37 1/4	BK						BK5		BK4		BK3		BK2		BK1		
BK2	6.5	55 3/4	37 1/4	37 1/4	BK								BK5		BK4		BK3		BK2	BK1	
ES	6	92 7/16	38 5/8		PFC				CF6		CF5		CF4		CF3		CF2		CF1		
ES	7	92 7/16	38 5/8		PFC						CF6		CF5		CF4		CF3		CF2	CF1	
ESD	6.25	86	35 1/2		PFC	CF6		CF5		CF4		CF3		CF2		CF1					
MM	7.25	84 3/8	33 15/16		PFC				CF6		CF5		CF4		CF3		CF2		CF1		
MM	8.5	84 3/8	33 15/16		PFC						CF6		CF5		CF4		CF3		CF2	CF1	
STALKER	8 1/8	88 1/8	36		PFC								CF6		CF5		CF4		CF3	CF2	CF1

*G3'S WITH THE NEW THIRD WHEEL HAVE A SMALL CABLE LENGTH OF 18 3/4".

Model	Brace	Peak Weight	Arrow Weight	Speed Testing																	
				23.5	24.0	24.5	25.0	25.5	26.0	26.5	27.0	27.5	28.0	28.5	29.0	29.5	30.0	31.0	32.0		
G3	6	70 lbs.	350 Grains				276		288		299		310		321		331				
G3	7	70 lbs.	350 Grains						276		288		299		310		321	331			
BK2	5.5	70 lbs.	350 Grains								314		326		338		350				
BK2	6.5	70 lbs.	350 Grains										314		326		338	350			
ES	6	70 lbs.	350 Grains				271		283		295		306		317		327				
ES	7	70 lbs.	350 Grains						271		283		295		306		317	327			
ESD	6.25	70 lbs.	350 Grains	265		274		285		295		304		314							
MM	7.25	70 lbs.	350 Grains				270		281		292		303		314		324				
MM	8.5	70 lbs.	350 Grains						270		281		292		303		314	324			
STALKER	8 1/8	70 lbs.	350 Grains								272		283		292		303	311	320		

*SUBTRACT 4-5 FPS FOR A 60LB BOW AND 9-11 FPS FOR A 50LB BOW.